

David Bronchalo Corral

Avda juan carlos I 38 28905-getafe

[JDS-TZ230C] Automatic peel and seal adhesive tape pasting machine

Issue date: 2024-10-05 Validity date: 30 days

MODEL AND NAME	Qty.	UNIT PRICE	Total Amount
MODEL AND NAME	Set	Transp.incluid	
[JDS-TZ230C] Automatic peel and seal adhesive tape pasting machine	1	28000 Eur	28000 Eur



PAYMENT TERMS	100% confir.
PORT OF LOADING	China
DELIVERY PERIOD	40 days upon receipt of deposit
PACKAGING	Plastic wrap film and wooden pallet or wooden case
INSTALLATION	All machines have been finished all adjustment in our workshop, the installation personnel is not needed. If buyer needs our engineer to install the machine in site, the charge (VISA, accommodation, food, round air-tickets and salary 100USD/day) shall be paid by the buyer in case.
ELECTRICAL EQUIPMENT	Unless noted, the machine needs electric of 380V, 3 Phase, 50/60 Hz. Consult factory for special electrical requirements.
WARRANTY	The maker makes guarantee that we supply the new (unused) machine, and we offer the warranty of 12 month. In this period, we will supply the free parts which are broken because of quality. We don't offer warranty for wrong operation (include changing software of PLC & HMI).



Product description

JDS-TZ230C full automatic envelope pressure-sensitive gumming machine is suitable for applying silicone tape on the seal flap of the finished envelope and folding the seal flap to close the envelope. Standard glue is pressure-sensitive adhesive. And double-sided tape can be used directly. The hot-melt glue is also available, but customers need pay for the hot melt adhesive system extra.

- 1. Reliable sheet separation
- 2. No-stop feeder
- 3. Easy regulation and paper positioning, accurate paper positioning
- 4. Ensuring under high speeds.
- 5. High quality electronic parts.
- 6. High Production efficiency.
- 7. Operator Friendly.

Technical parameter

Model	JDS-TZ230C	
Paper thickness	60-200gsm	
Size ranges of	Min.100mm x 90mm	
envelopes/paper	Max.490mm x 360mm	
Size ranges of tape	Min.10mm x 50mm	
	Max.40mm x 360mm	
Output per hour	3000-12000 pieces	
Connected load	6.0kw	
Weight	2000kg	
Dimensions	3500x1500x1400mm	

Sample show

